

# FLOS

## Glo-Ball S1 (Halogen) - Specification Sheet by Jasper Morrison, 1998

Mounting	Ceiling Pendant
Lamp (Bulb) Description	1 x 100W T8 E26 Base Frosted Halogen (Included)
Canopy Dimension	Diameter 5.75" - 1.40" high
Environment	Indoor - Dry Location
Dimming	Phase-cut Dimming / Triac Type
Finish	Opal
Technical and Product Description	GLO-BALL S pendant lamp providing diffused light. Diffuser consisting of an externally acid-etched, hand blown, flashed opaline glass. Transparent, injection molded polycarbonate diffuser support. 30% fiberglass reinforced injection-molded polyamide rose; pressed and galvanized ceiling fitting. Steel suspension cable.

### Electrical

Voltage	120
IP Rating	IP20

### Physical

Cord Length (inches)	106" - Clear
Construction Material	Glass
Weight	5.95 lbs



## CONTEXT

ENQUIRIES  
info@contextgallery.com


Tel. 404. 477. 3301  
Tel. 800. 886.0867

contextgallery.com  
contextcontract.com



FU300561 Opal

### Dimensional Image



### Certifications



### Lamping (Bulb)



100W T8 E26 Base Frosted Halogen

### Lamping (Bulb)



LED018 PRO-T38LED 14W 120V E26 2700K  
DIMM - 1800lm - CR180 Additional

### Lamping (Bulb)



LED031 PRO-T38LED 14W 120V E26 3000K  
Dimmable - 1800lm - CR180- Additional

# FLOS

## Glo-Ball S2 (Halogen) - Specification Sheet by Jasper Morrison, 1998

Mounting	Ceiling Pendant
Lamp (Bulb) Description	1 x 150W T-8 Medium Frosted Halogen (Included)
Canopy Dimension	Diameter 5.75" - 1.40" high
Environment	Indoor - Dry Location
Dimming	Phase-cut Dimming / Triac Type
Finish	Opal
Technical and Product Description	GLO-BALL S pendant lamp providing diffused light. Diffuser consisting of an externally acid-etched, hand blown, flashed opaline glass. Transparent, injection molded polycarbonate diffuser support. 30% fiberglass reinforced injection-molded polyamide rose; pressed and galvanized ceiling fitting. Steel suspension cable.

### Electrical

Voltage	120
IP Rating	IP20

### Physical

Cord Length (inches)	106" - Clear
Construction Material	Glass
Weight	12.35 lbs



FU301061 Opal

### Dimensional Image



### Certifications



### Lamping (Bulb)



150W T8 E26 Frosted Halogen

### Lamping (Bulb)



LED018 PRO-T38LED 14W 120V E26 2700K  
DIMM - 1800lm - CRI80 Additional

### Lamping (Bulb)



LED031 PRO-T38LED 14W 120V E26 3000K  
Dimmable - 1800lm - CRI80- Additional

# FLOS

## Glo-Ball S1 (Fluorescent) - Specification Sheet by Jasper Morrison, 1998

Mounting	Ceiling Pendant
Lamp (Bulb) Description	1 x 26W PL G24Q-3 Fluorescent (Included)
Canopy Dimension	Diameter 6.3" - 1.9" high
Environment	Indoor - Dry Location
Dimming	Not dimmable
Finish	Opal
Technical and Product Description	GLO-BALL S pendant lamp providing diffused light. Diffuser consisting of an externally acid-etched, hand blown, flashed opaline glass. Transparent, injection molded polycarbonate diffuser support. 30% fiberglass reinforced injection-molded polyamide rose; pressed and galvanized ceiling fitting. Steel suspension cable.

### Electrical

Voltage	120
IP Rating	IP20


### Physical

Cord Length (inches)	106" - Clear
Construction Material	Glass
Weight	5.95 lbs



FU300361 Opal

### Dimensional Image



### Certifications



### Lamping (Bulb)



26W PL G24Q-3 Fluorescent