


FLOS

In Vitro Ceiling Black 11W, 1150lm, 2700K, CRI 80 Integral Not dimmable LED driver UL - Specification Sheet by Philippe Starck, 2020

Mounting	Ceiling
Lamp (Bulb) Description	LED 13W, 1387lm, 2700K, CRI 80
Canopy Dimension	667
Environment	Outdoor - Wet location
Dimming	Not dimmable
Finish	Black
Technical and Product Description	Lighting outdoor collection with diffuse light for exterior ground installation. Integral opalescent diffuser and external protection in transparent borosilicate glass. The structure is made of die-cast and extruded aluminum treated with a chemical conversion process for effective resistance to atmospheric agents.

The body is powder coated and comes in various finishes. Integrated LED light source with Edge Lighting optical technology to guarantee perfect uniform lighting. Integrated 120V ON/OFF or dimmable electrical power supply.



● F018C25AU30 Black


Electrical

Voltage	120-277
IP Rating	IP65

Physical

Supply	LED driver
Construction Material	Aluminum, Glass
Weight	2.8 lbs

Dimensional Image



IN VITRO CEILING

Certifications



CONTEXT

ENQUIRIES
info@contextgallery.com

Tel. 404. 477. 3301
Tel. 800. 886.0867

contextgallery.com
contextcontract.com




FLOS

In Vitro Ceiling Forest Green 11W, 1150lm, 2700K, CRI 80 Integral 0-10V LED driver UL - Specification Sheet by Philippe Starck, 2020

Mounting	Ceiling
Lamp (Bulb) Description	LED 13W, 1387lm, 2700K, CRI 80
Canopy Dimension	667
Environment	Outdoor - Wet location
Dimming	0-10V
Finish	Terracota
Technical and Product Description	Lighting outdoor collection with diffuse light for exterior ground installation. Integral opalescent diffuser and external protection in transparent borosilicate glass. The structure is made of die-cast and extruded aluminum treated with a chemical conversion process for effective resistance to atmospheric agents.

The body is powder coated and comes in various finishes. Integrated LED light source with Edge Lighting optical technology to guarantee perfect uniform lighting. Integrated 120V ON/OFF or dimmable electrical power supply.



 F018C25BU25 Terracota


Electrical

Voltage	120-277
IP Rating	IP65

Physical

Supply	LED driver
Construction Material	Aluminum, Glass
Weight	2.8 lbs

Dimensional Image



IN VITRO CEILING

Certifications



CONTEXT

ENQUIRIES
info@contextgallery.com

Tel. 404. 477. 3301
Tel. 800. 886.0867

contextgallery.com
contextcontract.com

