

Drop

Design: Anderssen & Voll

Type: Upholstery

Composition: 60% new wool, 20% nylon, 20% polyester

Yarn type: Worsted Binding: Knit

Width: approx. 140 cm, 55 inches Weight: approx. 1.080 g/lin.m, 35 oz/ly

Repeat: none

Colour difference may occur Foreign fibers may occur in light colours

Cleaning: Vacuuming clean gently, ideally every week. Washable at 30°C if loose covers. Flat drip drying

More info: Care and maintenance kvadrat.dk

 $\underline{30} \times \underline{\otimes} \overline{\Box} \mathbb{P}$











DROP

Abrasion

Approx. 80.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling

Note 5, EN ISO 12945

Lightfastness

Note 5 - 6-7, ISO 105-B02

Fastness to rubbing

Dry note 4-5 / 5, ISO 105-X12 Wet note 4-5 / 5, ISO 105-X12

Absorption

0.4 Class D (flat)

Airflow

176 Pa s/m EN 29035

Flame resistance

AS/NZS 3837 class 3
ASTM E84 Class A Unadhered
BS 5852 part 1 ignition source 0
BS 5852 Crib 5, with treatment*
DIN 4102-B2
EN 1021-1/2
IMO FTP Code 2010 part 8
UNI 9175 1IM
US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

* To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants

CONTEXT

ENQUIRIES info@contextgallery.com

Tel. 404. 477. 3301 Tel. 800. 886.0867

contextgallery.com

ACT Guidelines Knit fabrics

Flammability

US Cal. Bull. 117-2013

Dry & Wet Crocking

Dry Crocking: Grade 5 Wet Crocking: Grade 4.5 - 5

Colour Fastness to Light

Grade 4.5-5 minimum 40 hours

Physical properties

Pilling Class 4-5 Breaking Strength wale 111 / course 286 lbs Seam Slippage wale 105 / course 118.5 lbs

Abrasion

100.000 cycles Martindale - High Traffic / Public Space

Benefits of wool

Wool is a renewable resource
Wool is very comfortable because of its ability to absorb/
give off humidity
Wool is flame retardant
Wool is biodegradable
Wool is naturally soil resistant
Wool ages with grace

Quality benefits

Great wear- and stretchability Very good abrasion Good lightfastness Flame retardant

Environmental benefits

REACH compliant
Follow the EU Ecolabel dye restrictions incl. AZO dye
and heavy metal restrictions
No use of halogen-based flame retardants (incl. brominated
and chlorinated)
No content of formaldehyde

Green building certificates

Greengard Gold: Low chemical emission Environmental product declaration (EPD): Based on a LCA following EN 15804 and follow the standard of ISO 14040 Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

The Netherlands

Launch

2019

Warranty

5 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information kvadrat.dk

CONTEXT

ENQUIRIES info@contextgallery.com

Tel. 404. 477. 3301 Tel. 800. 886.0867

contextgallery.com