



## Sisu

### Abrasion

Approx. 70.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

### Pilling

Note 3-4, EN ISO 12945

### Seam slippage

Seam parallel to warp: 1.5 mm parallel to weft: 3 mm  
EN ISO 13 936-2 180 Newton

### Snagging

Note 1 (Note 1-4, 1 best note) ICI Test method FAB 29, Tumble-Box

### Lightfastness

Note 5-7 ISO 105-B02

### Fastness to rubbing

Dry note 4-5 ISO 105-X12  
Wet note 4-5 ISO 105-X12

### Flame resistance

AS/NZS 3837 class 2  
ASTM E84 Class B Adhered  
ASTM E84 Class B Unadhered  
BS 5852 crib 5 with treatment \*  
BS 5852 part 1  
EN 1021-1/2  
IMO FTP Code 2010 Part 8  
NF D 60 013  
SN 198 898 5.3 with treatment \*  
UNI 9175 1IM  
US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

### Sisu

Design: Nanna Ditzel

Type: Upholstery

Composition: 91% Norwegian wool, 8% New Zealand wool, 1% nylon

Yarn type: Woolen

Binding: Panama

Width: Approx. 142 cm, 56 inches

Weight: Approx. 1,100 g/lin.m, 35.5 oz/ly

Foreign fibers may occur in light colours

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year warranty



# kvadrat

## CONTEXT

ENQUIRIES  
info@contextgallery.com

Tel. 404. 477. 3301  
Tel. 800. 886.0867

contextgallery.com

## ACT Guidelines Woven fabrics

### Flammability

US Cal. Bull. 117-2013

### Dry & Wet Crocking

Dry Crocking: Grade 3.5

Wet Crocking: Grade 4.5

### Colour Fastness to Light

Grade 5.0 minimum 40 hours

### Physical properties

Pilling Class 3-4

Breaking Strength warp 109 / weft 141 lbs.

Seam Slippage warp 19 / weft 24 lbs. (Fail)

### Abrasion

70.000 cycles Martindale – High Traffic / Public Spaces

### Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/  
give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

### Quality benefits

Complies with Möbelfakta

Very good abrasion

Good lightfastness

Flame retardant

### Green building certificates

Greenguard Gold: Low chemical emission

Environmental Product Declaration (EPD): Based on a LCA  
following EN 15804 and follow the standard of ISO 14040

Health Product Declaration (HPD): Declaring textile content  
and substance

### Country of origin

Norway

### Launch

2021

### Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard  
material is FSC certified and / or contains recycled content.

For further information

kvadrat.dk

### Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and  
heavy metal restrictions

No content of PFCs or 'PFAS'

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

# kvadrat

# CONTEXT

ENQUIRIES

info@contextgallery.com

Tel. 404. 477. 3301

Tel. 800. 886.0867

contextgallery.com