

## SAHCO

1831

ENQUIRIES  
 info@contextgallery.com  
 Tel. 404. 477. 3301  
 Tel. 800. 886.0867  
 contextgallery.com

**Baru**

Type: Upholstery

Composition: 87% wool, 10% polyester, 3% nylon

Yarn type: Worsted

Binding: Sateen Boucle

Width: Approx. 140 cm, 55 inches

Weight: Approx. 700 g/lin.m, 25 oz/ly

Repeat: None

Foreign fibers may occur in light colours


Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.

Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary.

Extraction cleaning might dissolve water based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see [www.kvadrat.dk/en/sahco](http://www.kvadrat.dk/en/sahco)



10<sup>year</sup>  
warranty



0575/23

**Abrasion**

Approx. 65.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

**Pilling**

Note 5, EN ISO 12945

**Seam slippage**

Seam parallel to warp: 2.0 mm, parallel to weft: 7.0 m  
 EN ISO 13 936-2 180 Newton

**Snagging**

Garde 1 ICI Testmethod FAB 29, Tumble-Box

**Lightfastness**

Note 4-6 ISO 105-B02

**Fastness to rubbing**

Dry note 4 ISO 105-X12

Wet note 3-4 ISO 105-X12

**Flame resistance**

BS 5852 Crib 5 with treatment \*

BS 5852 Part 1

EN 1021-1/2

IMO FTP Code 2010 Part 8

US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmental friendly alternatives but for now the external finisher may use a treatment containing halogen based flame retardants.*

## ACT Guidelines Woven fabrics

### Flammability

US Cal. Bull. 117-2013

### Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 4-5

Wet Crocking: Grade 4-5

### Colour Fastness to Light AATCC 16

Grade 4.5 minimum 40 hours

### Physical properties

Pilling ASTM D3511 Class 4

Seam Slippage ASTM D4034 warp 12 / weft 19 lbs

### Abrasion ASTM D4966

65.000 cycles Martaindale – High Traffic

### Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/  
 give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

### Quality benefits

Complies with Möbelfakta

Very good abrasion

Very good lightfastness

Flame retardant

Washable

### Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye  
 and heavy metal restrictions

No use of halogen based flame retardants (incl. brominated  
 and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

### Green building certificates

Greenguard Gold: Low chemical emission

Environmental Product Declaration (EPD): 3rd Party  
 Verified. ISO 14025 & EN 15804. Developed in accordance  
 with the European standard EN 15804+A2.

Health Product Declaration (HPD): Declaring textile  
 content and substance

### Country of origin

Norway

### Launch

2021

### Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard  
 material is FSC certified and / or contains recycled  
 content.

For further information

[www.kvadrat.dk/en/sahco](http://www.kvadrat.dk/en/sahco)