

## SAHCO

1831

ENQUIRIES  
 info@contextgallery.com  
 Tel. 404. 477. 3301  
 Tel. 800. 886.0867  
 contextgallery.com

**Nympha**

Type: Upholstery

Composition: 75% recycled cotton, 25% polyester

Yarn type: Staple / Filament

Binding: Plain weave / print

Width: Approx. 139 cm, 55 inches

Weight: Approx. 700 g/lin.m, 23 oz/ly

Repeat: Approx. 38 cm, 15 inchesV / 92 cm, 36 inches H

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.

Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary.

Extraction cleaning might dissolve water based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see [www.kvadrat.dk/en/sahco](http://www.kvadrat.dk/en/sahco)



10<sup>year</sup>  
warranty

**Abrasion**

Approx. 75.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

**Pilling**

Note 3-4, EN ISO 12945

**Seam slippage**

Seam parallel to warp: 2.0 mm, parallel to weft: 2.0 mm  
 EN ISO 13 936-2 180 Newton

**Lightfastness**

Note 3-6 ISO 105-B02

**Fastness to rubbing**

Dry note 4 ISO 105-X12

Wet note 3-4 ISO 105-X12

**Flame resistance**

BS 5852 Crib 5 with treatment \*

BS 5852 part 1 ignition source 0

EN 1021-1/2

US Cal. Bull. 117-2013 with Cal. 117 compliant interliner

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmental friendly alternatives but for now the external finisher may use a treatment containing halogen based flame retardants.*

# SAHCO

1831

ENQUIRIES  
info@contextgallery.com  
Tel. 404. 477. 3301  
Tel. 800. 886.0867  
contextgallery.com

## ACT Guidelines Woven fabrics

### Flammability

US Cal. Bull. 117-2013 with Cal. 117 compliant interliner

### Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 4,5

Wet Crocking: Grade 3,5

### Colour Fastness to Light AATCC 16

Grade 4,5 minimum 40 hours

### Physical properties

Pilling ASTM D3511 Class 4,5

Breaking Strength ASTM D5034 warp 221 / weft 125 lbs

Seam Slippage ASTM D4034 warp 77,5 / weft 91,5 lbs

### Abrasion ASTM D4966

75.000 cycles Martaindale – High Traffic

### Benefits of cotton

Cotton is a natural material and a renewable resource

Cotton is biodegradable

Cotton comfortable

### Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No use of halogen based flame retardants (incl. brominated and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

## Green building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

## Country of origin

Italy

## Launch

2022

## Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

[www.kvadrat.dk/en/sahco](http://www.kvadrat.dk/en/sahco)