

## SAHCO

1831

ENQUIRIES  
info@contextgallery.comTel. 404. 477. 3301  
Tel. 800. 886.0867

contextgallery.com

**Oaxaca**

Type: Upholstery

Composition: 100% cotton

Yarn type: Staple

Binding: Dobby

Width: Approx. 146 cm, 57 inches

Weight: Approx. 700 g/lin.m, 29 oz/ly

Repeat: None

Foreign fibers may occur in light colours

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.

Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary.

Extraction cleaning might dissolve water based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see [www.kvadrat.dk/en/sahco](http://www.kvadrat.dk/en/sahco)10<sup>year</sup>  
warranty**Abrasion**

Approx. 45.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

**Pilling**

Note 4, EN ISO 12945

**Seam slippage**Seam parallel to warp: 2.0 mm, parallel to weft: 2.0 mm  
EN ISO 13 936-2 180 Newton**Lightfastness**

Note 3-6 ISO 105-B02

**Fastness to rubbing**

Dry note 4-5 ISO 105-X12

Wet note 3 ISO 105-X12

**Flame resistance**

BS 5852 Crib 5 with treatment \*

BS 5852 part 1 ignition source 0

EN 1021-1/2

US Cal. Bull. 117-2013 with Cal. 117 compliant interliner

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmental friendly alternatives but for now the external finisher may use a treatment containing halogen based flame retardants.*

# SAHCO

1831

ENQUIRIES  
info@contextgallery.comTel. 404. 477. 3301  
Tel. 800. 886.0867

contextgallery.com

**ACT Guidelines Woven fabrics****Flammability**

US Cal. Bull. 117-2013 with Cal. 117 compliant interliner

**Dry & Wet Crocking AATCC 8**

Dry Crocking: Grade 4.0

Wet Crocking: Grade 3.0

**Colour Fastness to Light AATCC 16**

Grade 3 minimum 40 hours

**Physical properties**

Pilling ASTM D3511 Class 4.5

Breaking Strength ASTM D5034 warp 148 / weft 124 lbs

Seam Slippage ASTM D4034 warp 79 / weft 41 lbs

**Abrasion ASTM D4966**

45.000 cycles Martaindale – High Traffic

**Environmental benefits**Follow the EU Ecolabel dye restrictions incl. AZO dye  
and heavy metal restrictionsNo use of halogen based flame retardants (incl. brominated  
and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

**Green building certificates**

Greenguard Gold: Low chemical emission

**Country of origin**

Italy

**Launch**

2021

**Warranty**

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard  
material is FSC certified and / or contains recycled  
content.

For further information

[www.kvadrat.dk/en/sahco](http://www.kvadrat.dk/en/sahco)